



Float Specifications

(nom. 0.150 wall)

<u>Float Size In Inches</u>	<u>Buoyancy</u>	<u>Weight</u>	<u>T/L Qty</u>	<u>Per Skid LTL</u>
#2072-08	350	42	493	22
#2436-08	205	26	768	22
#2448-08	290	26	624	22
#3648-08	460	35	408	11
#2096-10	670	49	315	16
#1636-12	190	23	800	21
#2436-12	300	26	544	14
#2448-12	390	31	416	14
#2460-12	480	35	331	14
#2496-12	880	55	208	14
#3048-12	540	38	340	7
#3636-12	495	33	288	7
#3648-12	620	41	272	7
#3660-12	750	49	216	7
#3672-12	950	57	168	7
#3696-12	1250	81	136	7
#4848-12	850	53	208	7
#4860-12	1070	67	160	7
#4872-12	1300	75	136	7
#4896-12	1750	103	104	7
#1872-16	640	41	256	10
#2436-16	390	26	408	10
#2448-16	530	35	312	10
#2460-16	670	43	246	10
#3636-16	620	39	240	5
#3648-16	820	49	204	5
#3660-16	1050	67	116	5
#3672-16	1270	69	126	5
#3696-16	1670	97	102	5
#4848-16	1140	62	156	5
#4860-16	1420	78	120	5
#4872-16	1720	91	102	5
#4896-16	2310	127	78	5
#2448-18	620	37	260	10
#3648-18	960	53	170	5
#1248-20	310	27	520	16
#2448-20	680	36	260	8
#3648-20	1050	54	170	4
#3660-20	1250	65	100	4
#3672-20	1580	81	101	4
#3696-20	2080	107	85	4
#4848-20	1430	70	130	4
#4860-20	1750	92	100	4
#4872-20	2120	117	85	4
#4896-20	2910	134	65	4
#1872-24	950	51	166	6
#2448-24	790	47	208	6
#3648-24	1260	63	136	3
#3672-24	1850	94	92	4
#3696-24	2540	117	68	3
#4848-24	1680	78	104	3
#4860-24	2100	98	80	3

<u>Float Size In Inches</u>	<u>Buoyancy</u>	<u>Weight</u>	<u>T/L Qty</u>	<u>Per Skid LTL</u>
#4872-24	2560	120	68	3
#4896-24	3450	160	52	3
#2496-28	1930	111	76	3

#3636-28	1050	55	106	2
#3648-28	1450	70	106	3
#3672-28	2150	98	53	3
#3696-28	2880	127	53	3
#4848-28	1880	99	82	2
#4872-28	3030	131	52	3
#4896-28	4060	165	44	3
#3648-32	1610	79	102	2
#3672-32	2430	111	51	2
#3696-32	3250	148	51	2
#4848-32	2190	96.2	78	2
#4872-32	3400	142	51	2
#4896-32	4440	185	39	2
#2448-36	1160	78	156	4
#3696-36	3730	153	51	2
#4848-36	2450	105	78	2
#4872-36	3880	179	51	2
#4896-36	5130	190	39	2
#36120-20	2800		65	4
#36120-24	3350	155	55	3
#36120-32	4398	190	30	2
#48120-20	3800	186	50	4
#48120-24	4560	190	40	3
#48120-32	5785	240	30	2

Flanged Floats:

#2448-08F	240	33	544	22
#2436-12F	240	37	624	14
#2448-12F	360	35	416	14
#3448-12F	550	51	278	7
#2436-16F	340	37	408	10
#2448-16F	480	42	312	10
#3648-16F	750	60	204	5
#4848-16F	1060	75	156	5
#4872-16F				
#2448-18F	530	43	260	10
#3648-18F	870	55	170	5
#2448-20F	600	45	360	8
#3648-20F	960	58	170	4
#4848-20F	1350	84	120	4
#3648-24F	1140	62	136	3
#4848-24F	1530	86	104	3

Note:

Premier Materials Technology, Inc.
800-262-2275 **763-785-1509 fax**
www.premiermaterials.com
info@premiermaterials.com

Rev 9/1/2023