



Float Specifications

(nom. 0.150 wall)

<u>MODEL</u>	<u>CF</u>	<u>Buoyancy</u>	<u>Weight</u>	<u>T/L Qty</u>	<u>Per Skid</u>
#2072-08	6.7	350	42	493	22
#2436-08		205			
#2448-08	8	290	26	624	22
#3648-08	8.1	460	35	408	11
#2096-10	11.2	670	49	315	
#1636-12	4	190	23	800	21
#2436-12	6	300	26	544	14
#2448-12	8	390	31	416	14
#2460-12		480			
#2496-12	16.1	880	55	208	14
#3048-12	10	540	38	340	7
#3636-12		495			
#3648-12	12	620	41	272	7
#3660-12		750			
#3672-12	18	950	57	168	7
#3696-12	24	1250	81	136	7
#4848-12	16	850	53	208	7
#4860-12	20	1070	67	160	7
#4872-12	24	1300	75	136	7
#4896-12	32	1750	103	104	7
#1872-16	12	640	41	256	10
#2436-16	8	390	26	408	10
#2448-16	10.7	530	35	312	10
#2460-16	11.7	670	43	246	10
#3636-16	12.1	620	39	240	5
#3648-16	16	820	49	204	5
#3660-16	20.2	1050	67	116	5
#3672-16	24	1270	69	126	5
#3696-16	32	1670	97	102	5
#4848-16	21.3	1140	62	156	5
#4860-16	26.7	1420	78	120	5
#4872-16	32	1720	91	102	5
#4896-16	42.7	2310	127	78	5
#2448-18	12	620	37	260	10
#3648-18	18.2	960	53	170	5
#1248-20	6.7	310	27	520	16
#2448-20	13.3	680	36	260	8
#3648-20	20	1050	54	170	4
#3660-20		1250			
#3672-20	30	1580	81	101	4
#3696-20	40	2080	107	85	4
#4848-20	26.7	1430	70	130	4
#4860-20	33.3	1750	92	100	4
#4872-20	40	2120	117	85	4
#4896-20	53.3	2910	134	65	4
#1872-24	18.1	950	51	166	6
#2448-24	16	790	47	208	6
#3648-24	24	1260	63	136	3
#3672-24	36	1850	94	92	4
#3696-24	48	2540	117	68	3
#4848-24	32	1680	78	104	3
#4860-24	40	2100	98	80	3

<u>MODEL</u>	<u>CF</u>	<u>Buoyancy</u>	<u>Weight</u>	<u>T/L Qty</u>	<u>Per Skid</u>
#4872-24	48	2560	120	68	3
#4896-24	64	3450	160	52	3
#2496-28	37.3	1930	111	76	3
#3636-28		1050		106	
#3648-28	28	1450	70	106	3
#3672-28	42.3	2150	98	53	3
#3696-28	56.4	2880	127	53	3
#4848-28		1880		82	
#4872-28	56.5	3030	131	52	3
#4896-28	72.3	4060	165	44	3
#3648-32	32	1610	79	102	2
#3672-32	48	2430	111	51	2
#3696-32	64	3250	148	51	2
#4848-32	43	2190	96.2	78	2
#4872-32	64	3400	142	51	2
#4896-32	86	4440	185	39	2
#2448-36		1160			
#3696-36	72.5	3730	153	51	2
#4848-36	48.4	2450	105	78	2
#4872-36	72.5	3880	179	51	2
#4896-36	96.7	5130	190	39	2
#36120-20		2800		65	4
#36120-24	60.5	3350	155	55	3
#36120-32	80	4398	190	30	
#48120-20	67	3800	186	50	4
#48120-24	80.6	4560	190	40	3
#48120-32	107.5	5785	240	30	2
Flanged Floats:					
#2448-08F	5.3	240	33	544	22
#2436-12F	4.6	240	37	624	14
#2448-12F	6.2	360	35	416	14
#2436-16F	8	340	37	408	10
#2448-16F	8.1	480	42	312	10
#3648-16F	13	750	60	204	5
#4848-16F	18	1060	75	156	5
#4672-16		1250			
#4872-16		1420			
#2448-18F	9.3	530	43	260	10
#3648-18F	14.6	870	55	170	5
#2448-20F	10.3	600	45	360	8
#3648-20F	16.2	960	58	170	4
#4848-20F	22.4	1350	84	120	4
#3648-24F	19.3	1140	62	136	3
#4848-24F	26.7	1530	86	104	3

Note: All prices can be change without notice
All prices FOB factory

Premier Materials Technology, Inc.
Minneapolis, MN. 55432
800-262-2275 763-785-1509 fax.
www.premiermaterials.com
info@premiermaterials.com

Rev 10/1/17